

# TOP COAT REFERENCE GUIDE

<b>Product</b>	<b>Description/Use</b>	<b>Application</b>	<b>Sheens</b>
AquaGard™ (Durasheen)	Hard, clear topcoat. for Walls, trim, and doors. Barrier coat for furniture and cabinet finishes. Use also as a concrete sealer. Seal coat over low quality latex paint for color glazing. Excellent bonding even to most plastics, ceramic tile, and glass. Thin with water: 20% maximum Recoat time: Minimum 2 hours Co-solvency: Moderate Chem/Water Resist: Good	Best applied by spray, but can be rolled or brushed. Best with two thin, even coats.	Dull Satin Gloss
AquaGard™ with UV (Durasheen™ with UV)	Hard, clear topcoat with ultra-violet protection. Thin with water: 20% maximum Recoat time: Minimum 2 hours Co-solvency: Moderate Chem/Water Resist: Good	Best applied by spray, but can be rolled or brushed. Best with two thin, even coats.	Dull Satin Gloss
AquaThane™ (DuraGard™)	Hard, clear topcoat for floors, hard-use surfaces, furniture tops, and kitchen cabinet doors. Use over one coat of AquaGard or SetCoat Clear. Excellent bonding qualities over Durasheen. Interior and exterior applications. Thin with water: 20% maximum Recoat time: Minimum 4 hours Co-solvency: High Chem/Water Resist: High	Brush, roller or spray. Best with two thin, even coats. Strong co-solvent can move color work when over-brushed or rolled.	Dull Satin Gloss

<b>Product</b>	<b>Description/Use</b>	<b>Application</b>	<b>Sheens</b>
C-500 SuperUrethane™	<p>Hard, clear topcoat for water resistance. Perfect for wet conditions such as kitchen, vanity countertops, and floors. Excellent bonding qualities over Durasheen. Must be applied over 1 coat of AquaGard™ or Setcoat Clear.</p> <p>Thin with water: 20% maximum  Recoat time: Minimum 4 hours  Co-solvency: Very High  Chem/Water Resist: High/Excellent</p>	<p>Brush, roller or spray. Best with two or three thin, even coats. Strong co-solvents can move color work when over-brushed or rolled.</p>	<p>Dull  Satin  Gloss</p>
ColorSeal™	<p>A softer clear topcoat. Finish coat over glazes and sensitive color work. Seals the decorative finishes without disruption and prepares surface for a more durable topcoat if needed.</p> <p>Thin with water: 30% maximum  Recoat time: Minimum 2 hours  Co-solvency: Low  Chem/Water Resist: Low/Good</p>	<p>Brush, roller or spray one thin coat</p>	<p>Satin  Gloss</p>
Dead Flat Varnish™	<p>Use when a no sheen finish is desired.</p> <p>Thin with water: 10-20% maximum  Recoat time: 4 hours  Co-solvency: High  Chem/Water Resist: High</p>	<p>Brush, roller or spray.  Best with two thin coats.</p>	<p>Dull</p>

<b>Product</b>	<b>Description/Use</b>	<b>Application</b>	<b>Sheens</b>
Finishing Paste™	Wipe-on finish paste for Stain & Seal. Interior Use Only Thin with water: 20% maximum Recoat time: 15-30 minutes Co-solvency: Moderate Chem/Water Resist: Good	Wipe on, let dry and buff.	Soft Gloss
Matte Wall Sealer™	Durable topcoat which dries to a frosty finish. Do not use over dark colors.		
O'Villa® Wax*	Hard wax polymer used to topcoat Olde World Fresco® and O'Villa Finishing Plaster. Gives an Old World waxed wall look. Wax can be colored with Faux Effects® colorants. Can be recoated without stripping.		
Varnish Plus™	Finish coat for furniture and cabinets. Meets durability/chemical resistance standards set forth by the Furniture, Kitchen Cabinet & Millwork Association. Thin with water: 10-20% maximum Recoat time: 4 hrs or wait 24 Co-solvency: High Chem/Water Resist: High	Developed especially for brush and spray application. Two thin, even coats are best.	Dull Satin Gloss

**\*Professional product requires certification.**